



LAWRENCE
LIVERMORE
NATIONAL
LABORATORY

Snowflake divertor configuration studies for NSTX-Upgrade

V. A. Soukhanovskii

November 15, 2011

53rd Annual Meeting of the APS Division of Plasma Physics
Salt Lake City, UT, United States
November 14, 2011 through November 18, 2011

Disclaimer

This document was prepared as an account of work sponsored by an agency of the United States government. Neither the United States government nor Lawrence Livermore National Security, LLC, nor any of their employees makes any warranty, expressed or implied, or assumes any legal liability or responsibility for the accuracy, completeness, or usefulness of any information, apparatus, product, or process disclosed, or represents that its use would not infringe privately owned rights. Reference herein to any specific commercial product, process, or service by trade name, trademark, manufacturer, or otherwise does not necessarily constitute or imply its endorsement, recommendation, or favoring by the United States government or Lawrence Livermore National Security, LLC. The views and opinions of authors expressed herein do not necessarily state or reflect those of the United States government or Lawrence Livermore National Security, LLC, and shall not be used for advertising or product endorsement purposes.

Snowflake divertor configuration studies for NSTX-Upgrade

V. A. Soukhanovskii (LLNL),


S. P. Gerhardt, R. Kaita, E. Kolemen, H. W. Kugel,

J. E. Menard (PPPL),

R. Maingi, A. G. McLean (ORNL),

and NSTX Research Team

53rd Annual Meeting of the APS Division of Plasma Physics
November 14–18, 2011, Salt Lake City, Utah




Columbia U
CompX
General Atomics
FIU
INL
Johns Hopkins U
LANL
LLNL
Lodestar
MIT
Nova Photonics
New York U
ORNL
PPPL
Princeton U
Purdue U
SNL
Think Tank, Inc.
UC Davis
UC Irvine
UCLA
UCSD
U Colorado
U Illinois
U Maryland
U Rochester
U Washington
U Wisconsin

Culham Sci Ctr
U St. Andrews
York U
Chubu U
Fukui U
Hiroshima U
Hyogo U
Kyoto U
Kyushu U
Kyushu Tokai U
NIFS
Niigata U
U Tokyo
JAEA
Hebrew U
Ioffe Inst
RRC Kurchatov Inst
TRINITI
NFRI
KAIST
POSTECH
ASIPP
ENEA, Frascati
CEA, Cadarache
IPP, Jülich
IPP, Garching
ASCR, Czech Rep

Snowflake divertor experiments in NSTX provide basis for PMI development toward NSTX-Upgrade


■ Snowflake divertor configuration in NSTX

- Three divertor coils, steady-state up to 600 ms
- Core H-mode confinement unchanged
- Core impurities reduced
- Steady-state divertor peak heat flux significantly reduced
 - Due to geometry effects and radiative detachment






■ Development of snowflake divertor configuration for NSTX-U

- Steady-state and transient heat flux mitigation and detachment
- Magnetic control and configuration development





Snowflake configuration formation was followed by radiative detachment



- $P_{SOL} \sim 3 \text{ MW}$ ($P_{NBI} = 4 \text{ MW}$)
- Attached divertor \rightarrow snowflake transition (still attached) \rightarrow snowflake + detachment
- $Q_{div} \sim 2 \text{ MW}$ \rightarrow $Q_{div} \sim 1\text{-}1.2 \text{ MW}$ \rightarrow $Q_{div} \sim 0.5\text{-}0.7 \text{ MW}$


Significant reduction of steady-state divertor heat flux observed in snowflake divertor





C III, CIV profiles
courtesy of F. Scotti

- Attached standard divertor -> **snowflake transition** -> **snowflake + detachment**
- More experiments and modeling needed to understand geometry vs radiative effects

Impulsive heat loads due to Type I ELMs are partially mitigated in snowflake divertor



Magnetic control of snowflake divertor configuration is being developed




- Many ways for the open-loop snowflake configuration to fail - need close-loop feedback control of coil currents
- Testing X-point tracking algorithm
 - Locate X-points and snowflake centroid
 - E. Kolemen, PP9.00022 : Control Development for NSTX and the Effects of Strong Shaping
- Implementation of 2nd X-point position control in Plasma Control System being considered
 - Collaboration between PPPL, LLNL and GA

M.A. Makowski and D. Ryutov, "X-Point Tracking Algorithm for the Snowflake Divertor"


Plasma material interface development is critical for NSTX-U success

- NSTX-U mission elements:
 - Advance ST as candidate for Fusion Nuclear Science Facility
 - Develop solutions for PMI
 - Advance toroidal confinement physics for ITER and beyond
 - Develop ST as fusion energy system
- Challenge for NSTX-U divertor
 - 2-3 X higher input power
 - $P_{NBI} < 12$ MW, $I_p < 2$ MA
 - 30-50 % reduction in n/n_G
 - 3-5 X longer pulse duration
- Projected NSTX-U peak divertor heat fluxes up to 25-40 MW/m²
 - Radiative divertor with impurity seeding, double null, high flux expansion (snowflake)



Four divertor coils should enable flexibility in boundary shaping and control in NSTX-U

- A variety of lower and both lower and upper divertor snowflake configurations are possible in NSTX-U with four coils per divertor
 - ISOLVER free-boundary Grad-Shafranov solver used
 - Four coils can be used to control up to four parameters (X-pts, OSP, etc)



Midplane flux surface	0.0	1.5 mm	3.0 mm	6.0 mm	9.0 mm
L_{tot} (m)	38.3	20.4	13.9	9.9	8.3
L_X (m)	16.5	4.0	2.2	1.6	1.5
Angle (deg.)	1.6	0.8	0.99	3.0	3.9

- X 2 in plasma wetted surface area and connection length vs standard divertor

Snowflake divertor experiments in NSTX provide good basis for PMI development in NSTX-Upgrade

- **FY 2009-2010 snowflake divertor experiments in NSTX**
 - Helped understand control of magnetic properties
 - Core H-mode confinement unchanged
 - Core and edge carbon concentration reduced
 - Divertor heat flux significantly reduced
 - Steady-state reduction due to geometry and radiative detachment
 - Encouraging results for transient heat flux handling
 - Combined with impurity-seeded radiative divertor

- **Outlook for snowflake divertor in NSTX-Upgrade**
 - 2D fluid modeling of snowflake divertor properties scaling
 - Edge and divertor transport, radiation, detachment threshold
 - Compatibility with cryo-pump and lithium conditioning
 - Magnetic control development
 - PFC development – PFC alignment and PFC material choice

Backup slides

Acknowledgements

D. D. Ryutov, T. D. Rognlien, M. V. Umansky (LLNL),
M. G. Bell, R. E. Bell, D. A. Gates, A. Diallo, S. P. Gerhardt,
R. Kaita, S. M. Kaye, E. Kolemen, B. P. LeBlanc, J. E. Menard,
D. Mueller, S. F. Paul, M. Podesta, A. L. Roquemore,
F. Scotti (PPPL),
J.-W. Ahn, R. Maingi, A. McLean (ORNL),
D. Battaglia, T. K. Gray (ORISE),
R. Raman (U Washington),
S. A. Sabbagh (Columbia U)

Supported by the U.S. DOE under Contracts
DE-AC52-07NA27344, DE AC02-09CH11466,
DE-AC05-00OR22725, DE-FG02-08ER54989.

Radiative and geometric mitigation of divertor heat flux will be needed for high-power density NSTX-Upgrade discharges


$$q_{pk} \simeq \frac{P_{heat} (1 - f_{rad}) f_{out/tot} f_{down/tot} (1 - f_{pfr}) \sin \alpha}{2\pi R_{SP} f_{exp} \lambda_{q_{||}}}$$

$$A_{wet} = 2\pi R f_{exp} \lambda_{q_{||}} \qquad f_{exp} = \frac{(B_p/B_{tot})_{MP}}{(B_p/B_{tot})_{OSP}}$$

- Radiative divertor with impurity seeding
- Double null configurations
- Snowflake configuration as laboratory of divertor physics

Poloidal divertor concept enabled progress in tokamak physics studies in the last 30 years

- Divertor challenge
 - Steady-state heat flux
 - present limit $q_{peak} \leq 10 \text{ MW/m}^2$
 - projected to $q_{peak} \leq 80 \text{ MW/m}^2$ for future devices
 - Density and impurity control
 - Impulsive heat and particle loads
 - Compatibility with good core plasma performance
- Spherical tokamak: additional challenge - compact divertor
- NSTX (Aspect ratio $A=1.4-1.5$)
 - $I_p \leq 1.4 \text{ MA}$, $P_{in} \leq 7.4 \text{ MW}$ (NBI), $P / R \sim 10$
 - $q_{peak} \leq 15 \text{ MW/m}^2$, $q_{||} \leq 200 \text{ MW/m}^2$
 - Graphite PFCs with lithium coatings





**National Spherical
Torus Experiment**

Snowflake divertor geometry attractive for heat flux mitigation

- Snowflake divertor
 - Second-order null
 - $B_p \sim 0$ and $\text{grad } B_p \sim 0$ (Cf. first-order null: $B_p \sim 0$)
 - Obtained with existing divertor coils (min. 2)
 - Exact snowflake topologically unstable
- Predicted geometry properties (cf. standard divertor)
 - Larger region with low B_p around X-point: ped. stability
 - Larger plasma wetted-area A_{wet} : reduce q_{div}
 - Larger X-point connection length L_x : reduce $q_{||}$
 - Larger effective divertor volume V_{div} : incr. P_{rad} , P_{CX}
- Experiments
 - TCV (F. Piras *et. al*, PRL 105, 155003 (2010))
 - NSTX


**Exact
snowflake
divertor**




snowflake-plus

D. D. Ryutov, PoP 14, 064502 2007


Connection length is increased x 2-3 in snowflake divertor w.r.t. standard divertor



Shot 141241,
EFIT02,
time: 0.905s,
normalized flux: 1.005





Shot 141240,
EFIT02,
time: 0.905s,
normalized flux: 1.005




Shot 141240,
EFIT02,
time: 0.905s,
normalized flux: 1.015

Plasma-wetted area and connection length are increased by 50-90 % in NSTX snowflake divertor



- These properties observed in first 30-50 % of SOL width
- B_{tot} angles in the strike point region: 1-2°, sometimes < 1°
 - Concern for hot-spot formation and sputtering from divertor tile edges


Good H-mode confinement properties and core impurity reduction obtained with snowflake divertor





- 0.8 MA, 4 MW H-mode
- $\kappa=2.1$, $\delta=0.8$
- Core $T_e \sim 0.8\text{-}1$ keV, $T_i \sim 1$ keV
- $\beta_N \sim 4\text{-}5$
- Plasma stored energy ~ 250 kJ
- $H_{98}(y,2) \sim 1$ (from TRANSP)
- Core carbon reduction due to
 - Type I ELMs
 - Edge source reduction
 - Divertor sputtering rates reduced due to partial detachment

Snowflake divertor with CD_4 seeding leads to increased divertor carbon radiation

- $I_p=0.9$ MA, $P_{\text{NBI}}=4$ MW, $P_{\text{SOL}}=3$ MW
- Snowflake divertor (from 0.6 ms)
 - Peak divertor heat flux reduced from 4-6 MW/m² to 1 MW/m²
- Snowflake divertor (from 0.6 ms) + CD_4
 - Peak divertor heat flux reduced from 4-6 MW/m² to 1-2 MW/m²
 - Divertor radiation increased further



Snowflake divertor heat flux consistent with NSTX divertor heat flux scalings




- Snowflake divertor (*): $P_{SOL} \sim 3-4$ MW, $f_{exp} \sim 40-60$, $q_{peak} \sim 0.5-1.5$ MW/m²
 - Low detachment threshold


T. K. Gray et. al, EX/D P3-13, IAEA FEC 2010

V. A. Soukhanovskii et. al, PoP 16, 022501 (2009)



Divertor profiles show low heat flux, broadened C III and C IV radiation zones in the snowflake divertor phase




- Heat flux profiles reduced to nearly flat low levels, characteristic of radiative heating
- Divertor C III and C IV brightness profiles broaden
- High- n Balmer line spectroscopy and CRETIN code modeling confirm outer SP detachment with $T_e \leq 1.5$ eV, $n_e \leq 5 \times 10^{20} \text{ m}^{-3}$
 - Also suggests a reduction of carbon physical and chemical sputtering rates



Steady-state asymmetric snowflake-minus configuration has been obtained in FY2010 experiments in NSTX




- Snowflake-minus with three coils (w/ reversed PF1B) transformed from a standard medium- δ LSN at ~ 500 ms
- Snowflake with three coils (w/ reversed PF1B) transformed from a standard high- δ LSN at ~ 500 ms



1D estimates indicate power and momentum losses are increased in snowflake divertor

- 1D divertor detachment model by Post
 - Electron conduction with non-coronal carbon radiation
 - Max $q_{||}$ that can be radiated as function of connection length for range of f_z and n_e
 - -> Greater fraction of $q_{||}$ is radiated with increased L_x
- Three-body electron-ion recombination rate depends on divertor ion residence time
 - Ion recombination time: $\tau_{ion} \sim 1-10$ ms at $T_e = 1.3$ eV
 - Ion residence time: $\tau_{ion} \leq 3-6$ ms in standard divertor, x 2 in snowflake
 - -> Greater parallel momentum sink




$$q_{||} = -\kappa_0 T_e^{5/2} \frac{\partial T_e}{\partial x}$$

$$\frac{\partial q_{||}}{\partial x} = -n_e n_z L_Z(T_e)$$



2D multi-fluid edge transport code UEDGE is used to study snowflake divertor properties

- Fluid (Braginskii) model for ions and electrons
- Fluid for neutrals
- Classical parallel transport, anomalous radial transport
- Core interface:
 - $T_e = 120 \text{ eV}$
 - $T_i = 120 \text{ eV}$
 - $n_e = 4.5 \times 10^{19}$
- $D = 0.25 \text{ m}^2/\text{s}$
- $\chi_{e,i} = 0.5 \text{ m}^2/\text{s}$
- $R_{recy} = 0.95$
- Carbon 3 %



2D modeling shows a trend toward reduced temperature, heat and particle fluxes in the snowflake divertor

- 2D multi-fluid code UEDGE
 - Fluid (Braginskii) model for ions and electrons
 - Fluid for neutrals
 - Classical parallel transport, anomalous radial transport
 - $D = 0.25 \text{ m}^2/\text{s}$
 - $\chi_{e,i} = 0.5 \text{ m}^2/\text{s}$



Core interface:
 • $T_{e,i} = 120 \text{ eV}$
 • $n_e = 4.5 \times 10^{19}$
 $R_{\text{recy}} = 0.95$
 Carbon 3 %

